

ADJUSTABLE LEVELLING FEET

HOW TO ORDER

STEP 01

SCREW MATERIAL

ZINC PLATED STEEL
STAINLESS STEEL



STEP 02

SCREW SOCKET SIZE

12 SOCKET - SUITED TO M8 - M12
15 SOCKET - SUITED TO M10- M20



STEP 03

THREAD SIZE & LENGTH

THREAD SIZES RANGE FROM
M8 - M20.

AVAILABLE THREAD LENGTHS:
25 - 225MM



STEP 04

PLASTIC BASES

MATCH YOUR BASE SOCKET SIZE
TO THE SAME SOCKET SIZE AS
YOUR SCREW.



CHOOSE YOUR BASE DIAMETER.
40MM TO 123MM AVAILABLE.

12 SOCKET - SUITED TO M8 - M12
15 SOCKET - SUITED TO M10- M20

HOT TIP: IT IS VERY IMPORTANT THAT THE SOCKET SIZE YOU CHOOSE FOR
YOUR SCREW (12 OR 15), MATCHES THE SOCKET SIZE OF YOUR BASE.

NEED MORE GRIP ON YOUR LEVELLING FEET?

OPTIONAL NON SKID RUBBER PAD AVAILABLE. MATCH THE DIAMETER OF YOUR BASE TO THE PAD YOU NEED.



PART NUMBER BREAKDOWN

SCREW PART NUMBER

ASS = ZINC PLATED STEEL
ASSS = STAINLESS STEEL
(EXAMPLE = ZINC PLATED SCREW)

050 = 50MM
THREAD LENGTH

↑
11-ASS15-10-050

↓
15 = SOCKET SIZE

↓
10 = M10 THREAD

STEP 05

BASE PART NUMBER

50 = DIAMETER SIZE

↑
11-FPB15-50

↓
15 = SOCKET SIZE

Hi-Q[®]
components